

Scraped Texture

Pumpable or Hand Applied

1. About the Product

1.1 Composition

High Grade Silica Sand	BS EN 13139
Limestone	BS EN 13139
Cement	BS EN 197-1
Lime	BS EN 459-1
Additives	BS EN 934-2
Pigments	BS EN 12878

Any water added on site should be clean and free from any contaminants.

1.2 Uses

External Rendering

1.3 Application

Pumpable or Hand

1.4 Delivery

20kg Bags	1 Tonne Bags
Mini Silos	Bulk Silos
Associated Pump Equipment	

1.5 Advantages of KingDrymix Products

- Purity of materials ensure low co-efficient of shrinkage
- Minimal risk of cracking
- Water resistant and extremely durable
- Guaranteed total consistency of mix and colour
- Customer service and technical backup
- Low maintenance many years life expectancy
- Efficient prompt deliveries
- Excellent adhesion
- Excellent workability

2. Manufacture

2.1 Plant

All materials are batched and tested in the latest state of the art plant with constant testing at all stages of the process. The plant is capable of handling all sizes of order with complete quality assurance.

2.1 Samples

Small desk top size samples can be provided for colour identifications and 20kg sample bags will always be provided to ensure contract agreement.

3. Performance

applied by hand: used in conjunction with our base coat; achieving a more uniformed colour. The render must be scraped in a circular motion with a KingDrymix scraping tool once it has set but not allowed to harden completely.

applied by pump: used as a one coat system through a machine but must be finished in the same way as by hand. Spray machine saves time and the water content is more consistent than applying by hand.

4. On-Site

This company provides the full range of packaging these materials. On site every solution is available from hand applying to transferring dry to pumping wet and any combination of these methods. We regularly demonstrate all these aspects.

5. Coverage

Guideline

Thickness (mm)	Coverage (kg/m ²)
6-8	Approx 8-10



Health & Safety Data is available on request and provided routinely with all deliveries. Standard terms and conditions are provided with all quotations.

For all enquiries call our hotline on 01294 555864